

FOCUS ON LED STRIP LIGHTING

- HIGH CRI LED
- COLOR CONSISTENCY
- HIGH EFFICACY
- COLOR PURITY

2216 Series Flexible led strip

420 LEDs/m 24w/m



12V: 14.3mm(100x)

24V: 57mm(25x)

Nano cased

IP20/IP62

silicone dropped

IP65

silicone cased

IP66

silicone poured

IP67

silicone enclosed

IP68

Low
Decay

Long
Lifespan
>35000 hrs

3
YEAR

LC-A1013

LC-A1708

LC-A2408

Part No.	LED/m	Volt(DC)	CRI (Ra)	W/WW(K)	Power ± 5%	lm/m ± 5%	IPXX
LC420-N2216-W/WW-12/24-IP20	420	12V 24V	80-95	6500 3500 5500 2700 4500 2400	24W/M	1950-2083	IP20
LC420-W2216-W/WW-12/24-IP65						1950-2083	IP65
LC420-W2216-W/WW-12/24-IP66						1950-2083	IP66
LC420-W2216-W/WW-12/24-IP67						1950-2083	IP67
LC420-W2216-W/WW-12/24-IP68						1950-2083	IP68

120°

-20°C~50°C
Operating Temp

5
SDCM

5 M/Rol